

Measurement Unlimited by The Imagination.

Ultrasonic Flowmeter
UW-10



intelligent
DIGITAL



Features

1. Multi-path System

Up to 4-path system is achievable for stable measurement on the even short-pipe run.

2. Multi-output Ports

2 Analog / 4 Contact output

3. 2 digital output

1port can be selectable for MODBUS protocol.

4. Easy Configuration

Menu driven 4-keys input / Graphical PC Configuration

5. Data Acquisition software (Online-LOG) available

PC software shows graphical trend as standard.

6. Off-line configuration available

PC software can be input all parameters without connection to main unit.


7. Logging

Support the Measurements are logging and Setting change logging.

Specifications

Measurement	Method	Ultrasonic pulse transit time difference method
	Diameter Range	DN 25mm ~ 6000mm
	Accuracy	±1.0% R.D. (V > 0.8m/s at DN ≥ 300mm) (V > 2m/s at DN ≤ 250mm)
	Repeatability	±0.3%
Output	Multi - path Measurement	4 - path (Max.)
	Analog output	2ports (Std.) / 2range output / Allowable load resistance 1kΩ Max
	Relay output	4ports (Std.) / Totalizing signals & Alarms
	Digital output	2ports (Std.) One - way / Inter - communication mode & Modbus (RS232C)
Main Unit	Protection Degree	IEC 60529 IP66
Transducer	Temperature Range	-25°C ~ 65°C
	Environmental Class	IEC 60529 IP67 (Option; IP68)
	Cable Length	300m Max. (Between Main Unit and Transducers)
Logging	Measurement logging	Date & Time, Flow rate, Totalize, Warning, Direction, Status etc total 10 data will be logged. (1 year storage in 10-minute intervals / more than 500,000 data)
	Setting change logging	Date & Time, Name and Value of changed parameter up to 1,000 Parameters
Function	Self - diagnostics & failure processing	Automatic Gain Adjustment (AGA function)
	Disturbance detection	Automatic Gain Control (AGC function)
	No echo receiving warning	Preset totalize start
	Full scale warning	Data retention
	Over range warning	Path fixing
	Low flow cut	Forward / Backward flow change processing
	Zero shift	Basic data display
	Span compensation	Error historic counter
	Filtering (Smoothing)	Mass indication
	Fixed analog output	Metric & English unit
Certified	EMC Directive 2014/30/EU, Low Voltage Directive 2014/35/EU, RoHS Directive RoHS2((2011/65/EU)+(EU)2015/863), KS C 9811, 9610-4-2~8, 11	

Design and specifications are subject to change without prior notice, and without any obligation on the part of the manufacturer.



TOKYO
KEIKI

TOKYO KEIKI INC.

www.tokyokeiki.jp/e/products/measurement/

Measurement Systems Company

Head Office

HANEDA INNOVATION CITY Zone B 1-1-4 Haneda Airport, Ohta-ku, Tokyo 144-8551 JAPAN

TEL: +81-3-3737-8664 FAX: +81-3-3737-8665